

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Identification of the substance	Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane
Registration number (REACH)	01-2119984314-33-0000
EC number	922-114-8
Index No	-
CAS number	64742-49-0
Additional relevant and available information	SPB 40/60 EA-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	manufacture of substances Distribution of substance Formulation & (re)packing of substances and mixtures Uses in Coatings Use in Cleaning Agents Use in laboratories
--------------------------	---

1.3 Details of the supplier of the safety data sheet

DHC Solvent Chemie GmbH
 Timmerhellstraße 28
 D-45478 Mülheim an der Ruhr
 Germany

Telephone: +49 (208) 9940-0
 Telefax: +49 (208) 9940-150

Competent person responsible for the safety data sheet	Vanessa Manz
e-mail (competent person)	productsafety@dhc-solvent.de

1.4 Emergency telephone number

Emergency information service

Poison centre	
Country	Telephone
United Kingdom	+44 1235 239670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
flammable liquid	Cat. 2	(Flam. Liq. 2)	H225
skin corrosion/irritation	Cat. 2	(Skin Irrit. 2)	H315
specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336
aspiration hazard	Cat. 1	(Asp. Tox. 1)	H304
hazardous to the aquatic environment - chronic hazard	Cat. 2	(Aquatic Chronic 2)	H411

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

Remarks

For full text of H-phrases: see SECTION 16.

The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 shall apply.

Supplemental hazard information

Supplemental hazard information.

EUH066 Repeated exposure may cause skin dryness or cracking.

The most important adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08, GHS09



Hazard statements

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 Do NOT induce vomiting.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction.

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statements - disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional labelling requirements

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

According to the results of its assessment, this substance is not a PBT or a vPvB.

Vapour heavier than air, may form an explosive mixture in air: it may be ignited at some distance away from the spill resulting in flashbacks. Flowing product can create electrostatic charge, resulting sparks may ignite or cause an explosion.

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Name of substance	Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane
Registration number (REACH)	01-2119984314-33-0000
EC number	922-114-8
CAS number	64742-49-0
Index No	-
Purity	100 %

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS
n-hexane	CAS No 110-54-3 EC No 203-777-6	1 - <3	Fam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361f STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411

For full text of abbreviations: see SECTION 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Do NOT induce vomiting. Rinse mouth with water (only if the person is conscious).

4.2 Most important symptoms and effects, both acute and delayed

Choking and suffocation risks. Narcotic effects. Deficits in perception and coordination, reaction time, or sleepiness.

4.3 Indication of any immediate medical attention and special treatment needed

none

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

carbon dioxide (CO₂), BC-powder, foam, alcohol resistant foam, water mist

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Solvent vapours are heavier than air and may spread along floors. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. May produce toxic fumes of carbon monoxide if burning.

Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO₂)

5.3 Advice for firefighters

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Keep containers cool with water spray.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Avoid inhaling sprayed product. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Take off immediately all contaminated clothing and wash it before reuse.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials. - covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Recommendations

- **Measures to prevent fire as well as aerosol and dust generation**

Use only in well-ventilated areas. Use local and general ventilation. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- **Warning**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- **Explosive atmospheres**

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- **Flammability hazards**

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

- **Ventilation requirements**

Use local and general ventilation. Ground/bond container and receiving equipment.

- **Packaging compatibilities**

Only packagings which are approved (e.g. acc. to ADR) may be used.
Suitable materials and coatings for container/equipment: Carbon Steel, Stainless Steel, Polyester, Polytetrafluoroethylene (PTFE), Polyvinyl Alcohol (PVA)
Unsuitable Materials and Coatings for container/equipment: Butyl Rubber, Natural Rubber, Ethylene-propylene-diene monomer (EPDM), Polystyrene, Polyethylene, Polyacrylonitrile.

7.3 Specific end use(s)

See attached exposure scenarios

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
DE	pentane, mixture of isomers		MAK	1,000	3,000	2,000	6,000	DFG
DE	Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane	64742-49-0	AGW		600		1,200	TRGS 900

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified).

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified).

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

Relevant DNELs/DMELs/PNECs and other threshold levels

• human health values

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	210 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
DNEL	1,474 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	105 mg/kg	human, oral	consumer (private households)	chronic - systemic effects
DNEL	105 mg/kg	human, dermal	consumer (private households)	chronic - systemic effects
DNEL	315 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
n-hexane	110-54-3	DNEL	11 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
n-hexane	110-54-3	DNEL	75 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

8.2 Exposure controls

Appropriate engineering controls

Technical measures and the appliance of appropriate working methods take priority over the use of personal protective equipment.

Safety and necessary control measures vary according to exposure conditions. Appropriate measures are:

Open windows, door, to allow sufficient ventilation. If this is not possible employ a fan to increase air exchange (see attached exposure scenarios).

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggle with side protection.

Skin protection

• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

Short-term contact with the skin: Disposable gloves

Long-term contact with the skin: Gloves with long cuffs

Check leak-tightness/impermeability prior to use.

• type of material

NBR: acrylonitrile-butadiene rubber, FKM: fluoro-elastomer

• material thickness

0,40 mm.

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Body protection:

Suitable protective clothing: Flame resistant clothing

Suitable safety shoes: Anti static safety shoes according to EN 345 S3

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

Respiratory protection

For activities in enclosed areas at elevated temperatures of the substance, local extraction or explosion protected ventilation equipment is recommended. In case this is not sufficient for the intended use, then apply a suitable respiratory protection according to EN 140 type A or better (see exposure scenarios).

Environmental exposure controls

Do not empty into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Colour	colourless
Odour	characteristic

Other physical and chemical parameters

pH (value)	not determined
Melting point/freezing point	<-90 °C (ASTM D 5950)
Initial boiling point and boiling range	36 – 83 °C (ASTM D 1078)
Flash point	<-20 °C bei 1013 mbar
Explosive limits	
• lower explosion limit (LEL)	1 vol%
• upper explosion limit (UEL)	7.4 vol%
Vapour pressure	43 kPa at 20 °C
Density	0.62 – 0.75 g/cm ³ at 20 °C
Solubility(ies)	
Water solubility	220 mg/l at 25 °C
Partition coefficient	
n-octanol/water (log KOW)	2.59 – 3.66
Auto-ignition temperature	260 °C
Viscosity	
• kinematic viscosity	0.45 mm ² /s at 20 °C (ASTM D7042)
Explosive properties	
in use, may form flammable/explosive vapour-air mixture	
Oxidising properties	none

9.2 Other information

There is no additional information.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

risk of ignition

• if heated

risk of ignition

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure (see below "Conditions to avoid").

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

Hints to prevent fire or explosion

Use only non-sparking tools.

10.5 Incompatible materials

oxidisers

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

May be harmful if inhaled.

Exposure route	Endpoint	Value	Species
oral	LD50	>2,000 mg/kg	rat
dermal	LD50	>3,350 mg/kg	rabbit
inhalation: vapour	LC50	>25.3 mg/l/4h	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

• Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

If on skin. If inhaled.

Other information

Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity (acute)

Endpoint	Value	Species	Exposure time
EC50	2.7 mg/l	aquatic invertebrates	48 h
LC50	4.26 mg/l	rainbow trout (Oncorhynchus mykiss)	96 h

Aquatic toxicity (chronic)

May cause long-term adverse effects in the aquatic environment.

Endpoint	Value	Species	Exposure time
NOELR	2.8 mg/l	rainbow trout	28 d
NOELR	4.888 mg/l	daphnia magna	21 d

12.2 Persistence and degradability

The substance is readily biodegradable.

12.3 Bioaccumulative potential

Data are not available.

n-octanol/water (log KOW) 2.59 – 3.66

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Other adverse effects

Data are not available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately re-conditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. **DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.**

List of wastes

Proposed waste code(s) for the used product:

07 01 04x Other organic solvents, washing liquids and mother liquors

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018


SECTION 14: TRANSPORT INFORMATION

14.1	UN number	3295
14.2	UN proper shipping name Technical name	HYDROCARBONS, LIQUID, N.O.S. Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane
14.3	Transport hazard class(es) Class	3 (flammable liquids)
14.4	Packing group	II (substance presenting medium danger)
14.5	Environmental hazards	hazardous to the aquatic environment
14.6	Special precautions for user Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	3295
Proper shipping name	HYDROCARBONS, LIQUID, N.O.S.
Particulars in the transport document	Special provision 640C
Class	3
Classification code	F1
Packing group	II
Danger label(s)	3 + "fish and tree"



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	640C
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
Emergency Action Code	3YE


• International Maritime Dangerous Goods Code (IMDG)

UN number	3295
Proper shipping name	HYDROCARBONS, LIQUID, N.O.S.
Particulars in the shipper's declaration	UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, -20°C c.c., MARINE POLLUTANT
Class	3
Marine pollutant	yes (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	3 + "fish and tree"

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018



Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	B
• International Civil Aviation Organization (ICAO-IATA/DGR)	
UN number	3295
Proper shipping name	Hydrocarbons, liquid, n.o.s.
Class	3
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	3



Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

• Restrictions according to REACH, Annex XVII

Name of substance	CAS No	Wt%	Type of registration	No
Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane		100	1907/2006/EC annex XVII	3
Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane		100	1907/2006/EC annex XVII	40

• List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

not listed

• 2012/18/EU (Seveso III)

No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200	500	57)

Notation

57) Hazardous to the Aquatic Environment in category Chronic 2.

• Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)

VOC content 100 %

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

• **Directive on industrial emissions (VOCs, 2010/75/EU)**

VOC content 100 %

• **Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II**

not listed

• **Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)**

not listed

• **Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)**

not listed

National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CA	NDSL	not listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	not listed
JP	ISHA-ENCS	not listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AICS	Australian Inventory of Chemical Substances.
CICR	Chemical Inventory and Control Regulation.
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS).
DSL	Domestic Substances List (DSL).
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP).
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China.
INSQ	National Inventory of Chemical Substances.
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS).
KECI	Korea Existing Chemicals Inventory.
NDSL	Non-domestic Substances List (NDSL).
NZIoC	New Zealand Inventory of Chemicals.
PICCS	Philippine Inventory of Chemicals and Chemical Substances.
REACH Reg.	REACH registered substances.
TCSI	Taiwan Chemical Substance Inventory.
TSCA	Toxic Substance Control Act.

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has been carried out.

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

SECTION 16: OTHER INFORMATION

16.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
6.1	For non-emergency personnel: Remove persons to safety. Avoid inhaling sprayed product. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Remove/take off immediately all contaminated clothing and wash it before reuse.	For non-emergency personnel: Remove persons to safety. Avoid inhaling sprayed product. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Take off immediately all contaminated clothing and wash it before reuse.
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW	Workplace exposure limit
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DFG	Deutsche Forschungsgemeinschaft MAK- und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer

Hydrocarbons, C5-C6, n-alkanes, isoalkanes, <5% n-hexane

Version number: GHS 3.0
Replaces version of: 13.10.2017 (GHS 2)

Revision: 05.06.2018

Abbr.	Descriptions of used abbreviations
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)
- The exposure scenarios are available at www.dhc-solvent.de in the Service section.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).
International Maritime Dangerous Goods Code (IMDG).
International Air Transport Association (IATA).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product. The information concerning legal regulations can lay no claim to completeness. In addition to this, other provisions may also apply to the product.